

In the Claims

Please replace claims 1-22 with the following claims

1-22:

1. A system for identifying a selected user from a first plurality of users, the system comprising:

a first grammar extractor having a first input operatively coupled to receive an identifier of one of the plurality of users, and a second input operatively coupled to receive a first utterance from the one of the first plurality of users uttered during a first session, the first grammar extractor for extracting a first speaker-dependent, text-dependent grammar from the first utterance received at the first grammar extractor first input and for providing at an output the first speaker-dependent, text-dependent grammar and the corresponding identifier received at the first input;

a grammar storage having an input/output coupled to the first grammar extractor output, for receiving the first speaker-dependent, text-dependent grammar and identifier for each of the plurality of users and storing the first speaker-dependent, text-dependent grammar responsive to the identifier, and for providing at the input/output one of

20 said first speaker-dependent, text-dependent grammars  
corresponding to an identifier responsive to receipt of  
said identifier at the grammar storage input/output;

a second grammar extractor having an input operatively  
coupled to receive a second utterance from the selected  
25 user uttered during a second session different from the  
first session, the second grammar extractor for extracting  
and providing at an output a second speaker-dependent,  
text-dependent grammar responsive to the second utterance  
received at the second grammar extractor input; and

30 a first recognizer having a first input coupled to the  
grammar storage input/output, and a second input coupled to  
the second grammar extractor output, the first recognizer  
for identifying a match between a set of a plurality of the  
first speaker-dependent, text-dependent grammars stored in  
35 the grammar storage and the second speaker-dependent, text-  
dependent grammar received at the second first recognizer  
input, and for providing at an output coupled to an  
apparatus output, the identifier of the user corresponding  
to a one of the first speaker-dependent, text-dependent  
40 grammar in the grammar storage most closely matching the  
second speaker-dependent, text-dependent grammar received  
at the first recognizer second input.

2. The system of claim 1, wherein the first utterance comprises a password of the one of the plurality of users, and the second utterance comprises a password of the user.

3. The system of claim 1, wherein the first grammar extractor is the second grammar extractor.

4. The system of claim 1, additionally comprising:

A second recognizer having an input operatively coupled to receive a third utterance uttered during the second session, the second recognizer for, responsive to the third utterance, identifying a second plurality of users from the first plurality of users as belonging in the set of users.

5. The system of claim 4, wherein the third utterance comprises a name of the user.

6. The system of claim 5, wherein the second recognizer identifies the second plurality of users responsive to the third utterance by recognizing the third utterance and comparing the recognized third utterance with a list of user identifiers of the first plurality of users.

7. The system of claim 6, additionally comprising:

a first voiceprint extractor having a first input operatively coupled to receive an identifier of one of the

first plurality of users and a second input operatively  
5 coupled to receive a fourth utterance from the one of the  
first plurality of users uttered during the first session,  
the first voiceprint extractor for creating a voiceprint  
responsive to the fourth utterance and for providing the  
voiceprint and the identifier of the user at an output;

10 a voiceprint storage having an input/output coupled to  
the first voiceprint extractor output, the voiceprint  
storage for storing, for each of the first plurality of  
users, the voiceprint received at the voiceprint storage  
input/output associated with the identifier of the user,  
15 and for providing a first voiceprint at the input/output  
responsive to a request for the voiceprint comprising the  
identifier of the user corresponding to the voiceprint  
received at the voiceprint storage input/output;

a second voiceprint extractor having an input coupled  
20 to receive a fifth utterance uttered by the selected user  
during the second session, the second voiceprint extractor  
for extracting and providing at an output a second  
voiceprint responsive to the fifth utterance; and

a verifier having a input/output coupled to the  
25 voiceprint storage input/output, a first input coupled to  
the second voiceprint extractor output for receiving the

second voiceprint, and a second input coupled to the first recognizer output, and an output coupled to the apparatus output, the verifier for providing at the input/output an  
30 identifier corresponding to the identifier received at the second input and receiving at the input/output one of the first voiceprints, said first voiceprint corresponding to the identifier provided at the input/output, the verifier additionally for comparing the first voiceprint received at  
35 the verifier input/output with the voiceprint received at the first verifier input and for signaling at an output coupled to the apparatus output responsive to said first voiceprint and said second voiceprint matching within an acceptable tolerance level.

8. The system of claim 7 wherein:

each fourth utterance comprises a sixth utterance uttered by one of the plurality of users during the first session and the first utterance; and

5 the fifth utterance comprises the second utterance and the third utterance.

9. The system of claim 8, wherein the sixth utterance comprises a name of one of the first plurality of users.

10. The system of claim 7 wherein the second voiceprint extractor is the first voiceprint extractor.

11. A method of identifying a caller as a user of a computer system, the method comprising:

receiving a first utterance;

extracting a speaker-dependent, text-dependent grammar  
5 from the first utterance;

comparing the speaker-dependent, text-dependent grammar extracted with a set of speaker-dependent, text-dependent grammars, each speaker-dependent, text-dependent grammar in the set of speaker-dependent, text-dependent grammars corresponding to a user;  
10

responsive to the comparing the speaker-dependent, text-dependent grammar step, identifying a set of at least one user, the number of users in set of at least one user smaller than the number of users corresponding to the speaker-dependent, text-dependent grammars in the set of  
15 speaker-dependent, text-dependent grammars; and

extracting a voiceprint from the first utterance;

comparing the voiceprint extracted with a voiceprint for each user in the set of at least one user; and

20 identifying the user responsive to the comparing the voiceprint step.

12. The method of claim 11, wherein the number of users in the set of at least one user is one.

13. The method of claim 11, additionally comprising:

receiving a second utterance from the caller;

recognizing the second utterance; and

identifying the set of speaker-dependent, text-

5 dependent grammars responsive to the recognizing the second utterance step.

14. The method of claim 13, wherein the recognizing step comprises speaker independent voice recognition of the second utterance.

15. (amended) The method of claim 13, wherein the recognizing step comprises speaker-dependent voice recognition of the second utterance.

16. The method of claim 13, wherein the extracting the voiceprint step comprises extracting the voiceprint from the first utterance and the second utterance.

17. A computer program product comprising a computer useable medium having computer readable program code embodied therein for identifying a caller as a user of a computer system, the computer program product comprising:

5 computer readable program code devices configured to  
cause a computer to receive a first utterance;

computer readable program code devices configured to  
cause a computer to extract a speaker-dependent, text-  
dependent grammar from the first utterance;

10 computer readable program code devices configured to  
cause a computer to compare the speaker-dependent, text-  
dependent grammar extracted with a set of speaker-  
dependent, text-dependent grammars, each speaker-dependent,  
text-dependent grammar in the set of speaker-dependent,  
15 text-dependent grammars corresponding to a user;

computer readable program code devices configured to  
cause a computer to, responsive to the computer readable  
program code devices configured to cause a computer to  
compare the speaker-dependent, text-dependent grammar,  
20 identify a set of at least one user, the number of users in  
set of at least one user smaller than the number of users  
corresponding to the speaker-dependent, text-dependent  
grammars in the set of speaker-dependent, text-dependent  
grammars;

25 computer readable program code devices configured to  
cause a computer to extract a voiceprint from the first  
utterance;



computer readable program code devices configured to  
cause a computer to compare the voiceprint extracted with a  
30 voiceprint for each user in the set of at least one user;  
and

computer readable program code devices configured to  
cause a computer to identify the user responsive to the  
comparing the voiceprint step.

18. The computer program product of claim 17, wherein  
the number of users in the set of at least one user is one.

19. The computer program product of claim 17,  
additionally comprising:

computer readable program code devices configured to  
cause a computer to receive a second utterance from the  
5 caller;

computer readable program code devices configured to  
cause a computer to recognize the second utterance; and

computer readable program code devices configured to  
cause a computer to identify the set of speaker-dependent,  
10 text-dependent grammars responsive to the recognizing the  
second utterance step.

20. The computer program product of claim 19, wherein  
the computer readable program code devices configured to

cause a computer to recognize comprise computer readable  
program code devices configured to cause a computer to  
5 perform speaker independent voice recognition of the second  
utterance.

21. The computer program product of claim 19, wherein  
the computer readable program code devices configured to  
cause a computer to recognize comprise computer readable  
program code devices configured to cause a computer to  
5 perform speaker-dependent voice recognition of the second  
utterance.

22. The computer program product of claim 19, wherein  
the computer readable program code devices configured to  
cause a computer to extract the voiceprint comprise  
computer readable program code devices configured to cause  
5 a computer to extract the voiceprint from the first  
utterance and the second utterance.

---